

DATA SHEET

Taurus XQ 350 Synergic DW EX

090-005649-00002



- MIG/MAG inverter welding machine including Expert XQ 2.0 control, with separate wire feeder
- Perfect MIG/MAG weld seams even with long welding leads
- Synergic control with one-knob operation

all in

No need to purchase additional characteristics – all characteristics for this machine type are included in the scope of delivery ex works

- With the innovative EWM Synergic characteristics rootArc[®] XQ, forceArc[®] XQ and superPuls
- With Synergic characteristics for GMAW standard welding for steel/CrNi/aluminium
- Non Synergic operation for manual setting of welding parameters
- Suitable for MMA welding, TIG welding and gouging
- Individually configurable programmes for each welding task (JOB)
- Adjustable start and end-crater functions
- Infinitely adjustable arc dynamics (choke effect)
- **Your benefits**
- flexFit casing system: Many accessory parts and options can be fixed to the welding machine using conventional slot nuts
- LED information bar: Indicates the current operating status
- Drive XQ / Drive XQ IC 200 with high-precision, powerful EWM eFeed 4-roll drive to reliably feed all solid and flux cored wires
- Energy-saving thanks to high efficiency and standby function
- Best suited for use with long hose packages
- Connection capability for remote control and function torch
- Easy, tool-free change of welding polarity
- Insulated wire space
- IP23 spray water protected
- Optional network connectivity with the ewm Xnet software via an integrated or external gateway
- PC interface for PC300 XQ software
- The high 1500 W cooling capacity, high-performance centrifugal pump and 8-litre coolant tank make for excellent torch cooling, resulting in cost savings on consumables
- Free WPQR package for certification up to and including EXC2 in accordance with EN 1090 and for welding of unalloyed steels up to and including S355

DATA SHEET

Taurus XQ 350 Synergic DW EX

| | |
|-----------------------------------|--|
| Version | Taurus XQ 350 Synergic DW EX |
| Setting range for welding current | 5 A - 350 A |
| Duty cycle 40 °C | 350 A / 100 % |
| Open circuit voltage | 82 V |
| Mains voltage (ex works) | 3 x 380 V - 400 V |
| Mains voltage (possible) | 3 x 440 V - 460 V |
| Mains voltage (possible) | 3 x 480 V - 500 V |
| Mains tolerances (ex works) | -25 % up to +20 % |
| Mains frequency | 50 Hz / 60 Hz |
| Recommended generator power | 18.8 kVA |
| Power consumption Pi | 24 W |
| Cooling capacity at 1 l/min. | 1000 W |
| Pump pressure | 3.5 bar |
| Tank capacity | 8 l |
| Protection classification | IP23 |
| Test mark |     |
| EMC class | A |
| Dimensions (L x B x H) | 1150 mm x 678 mm x 972 mm 45.3 inch x 26.7 inch x 38.3 inch |
| Weight | 125.5 kg / 276.7 lbs |
| Standards | IEC 60974-1, -2 and -10 CL.A |

Configurations

| Item no. | Designation |
|------------------|---|
| 090-005649-00000 | Taurus XQ 350 Synergic D. Multiprocess MIG/MAG welding machine including all characteristics and welding processes, |
| 092-003303-00000 | OW F06W. Water cooling |
| 092-003307-00000 | OW Expert XQ 2.0. Expert XQ 2.0 control |
| 092-003316-00000 | OW F06R1. Wheel kit with single cylinder mount |
| 092-003349-00000 | OW MCord 6 mm ² 5m. Mains connection lead, 5 m |