

## WEA 17-125 Quick (600534000) Angle grinder (220-240 V / 50 - 60 Hz); Cardboard box

Order no. 600534000 EAN 4007430246073



Product may differ from Image



- Maximum productivity: 1,700 Watt angle grinder with the power of a large grinder and the compactness of a small one for quickest material removal on industrial applications
- Longer service life, more power: the Metabo Marathon-motor with patented dust protection, up to 20% more overload capacity and 50% more torque
- Tacho Constamatic (TC) Full-wave Electronics: fast work progress by means of constant speed under load
- Tool free, fast disc change at the touch of a button with the Metabo M-Quick-System
- Tool-free adjustable guard; twist-proof
- Low-vibration side handle Metabo VibraTech (MVT)
- Best anti-vibration system: integrated auto-balancer for up to 50% less hand-arm vibrations, longer service life of the machine and up to twice the service life of the grinding wheels
- Metabo S-automatic mechanical safety clutch: minimises kick-back to the lowest level when the disc jams unexpectedly for maximum user safety and swift progress
- Electronic overload protection, soft start and restart protection
- Gear housing can be unscrewed, rotated in 90° steps and remounted for left-handed operation or cutting
- Auto-stop carbon brushes to protect the motor



## Technical data

## Characteristics

Disc-Ø	125 mm
Rated input power	1700 W
Output power	1040 W
No-load speed	11000 rpm
Speed at rated load	11000 rpm
Torque	3.7 Nm
Spindle thread	M 14
Handle circumference	206 mm
Weight (without power cable)	2.5 kg
Cable length	4 m
Vibration	
Surface grinding	4 m/s <sup>2</sup>
Uncertainty of measurement K	1.5 m/s <sup>2</sup>
Grinding with sandpaper	3 m/s <sup>2</sup>
Grinding with sandpaper Uncertainty of measurement K	3 m/s <sup>2</sup> 1.5 m/s <sup>2</sup>
Uncertainty of measurement K	
Uncertainty of measurement K Noise emission	1.5 m/s²

## Scope of delivery

Guard Inner support flange M-Quick flange nut Metabo VibraTech (MVT) side handle