



Optional



JWC-05
Water Cooler

Technical Data

Input Voltage	AC 230V - 50/60 Hz
I _{eff} (A)	28.9
Input Power (kVA)	12.1
Voltage Adjustment Range (V)	11 - 29
Current Range (A)	30 - 270
Duty Cycle @ 40°C	270A @ 30%
No-Load Voltage (V)	54
Wire Speed (m/min)	0 - 16
Efficiency (%)	85
Power Factor	0.75
Protection/Insulation Class	IP21S/F
Dimensions (LxWxH mm)	1020 x 505 x 1460
Weight (Kg)	101

Key Features

- Single phase IGBT inverter
- High powered 230V machine
- Digital Amp & Voltmeter
- 4 roll wire feed unit
- High Duty Cycle - single phase inverter
- Advanced control circuitry
- Suitable for 0.6, 0.8, 1.0 and 1.2mm welding wire
- Burn back control & wire inching
- 2T/4T trigger function
- Power & status LED's
- Gas check function
- Variable inductance
- Inverter trolley takes full size gas bottle
- MIG/MAG/MMA

Package Includes

Inverter power source, Trolley, 4 roll wire feed unit, 5 mtr Interconnecting cable, MIG welding torch, Work return lead and clamp, Gas hose & regulator, Operating Instructions, 5 year warranty*



* 5 year warranty subject to product registration